



# Univox® GO TALK

GTA-CT6 / GTA-CT12 / GTA-CC24

## Features

- Convenient storage and charging for up to 6 (GTA-CT6) or 12 (GTA-CT12) units; transportation, storage, and charging available for up to 24 (GTA-CC24) units
- Specifically designed for GoTalk Transceivers
- Custom-fit pockets with USB-C connectors ensure secure storage
- Easy setup with included PSU; GTA-CT12 features an on/off button for power conservation when not in use

## Charging trays and cases

The GoTalk GTA-CT6 and GTA-CT12 Charging Trays, along with the GoTalk GTA-CC24 Charging Case from Univox, are specifically designed to provide a convenient solution to charge, store and transport your GoTalk transceivers. These chargers feature custom-fit pockets with USB-C connectors to securely hold the transceivers in place.

The charging trays are easy to set up. Place them on a table, desk, or shelf, plug the PSU into a wall socket, and you're good to go. The GTA-CT12 sports an on/off button to reduce power consumption when the system is fully charged but not in use.

The GTA-CC24 charging case offers plenty of space to store up to 24 transceivers. An external DC power input with a dust cover ensures that you can charge your devices easily between uses. Additionally, the charging case offers multiple pockets and compartments to store your accessories.

**Note:** Both the GTA-CT6 and GTA-CT12 charging trays come with a wall plug PSU and adapters for EU, US, UK, and AUS sockets. The GTA-CC24 charging case includes a PSU and a separate country-specific power cord for added convenience.



## Specifications

---

### PHYSICAL

|                      |   |                        |                          |
|----------------------|---|------------------------|--------------------------|
| Case Color:          | Aluminium/grey (CC24)   |                        |                          |
| Tray Color:          | Black (CT6/CT12/CC24)   |                        |                          |
| Dimensions:          | CT6: 44 x 170 x 85 mm (1.73 x 6.69 x 3.35 in.)<br>CT6: 53 x 115 x 218 mm (2.09 x 4.53 x 8.58 in.)<br>CC24: 208 x 456 x 343 mm (8.19 x 17.95 x 13.50 in.)  |                        |                          |
| Shipping Dimensions: | CT6: 236 x 208 x 50 mm (9.29 x 8.19 x 1.97 in.)<br>CT12: 271 x 247 x 56 mm (10.67 x 9.72 x 2.2 in.)<br>CC24: 470 x 364 x 227 mm (18.5 x 14.33 x 8.94 in.) |                        |                          |
| Net Weight:          | CT6: 203 g (0.45 lbs)   | CT12: 306 g (0.67 lbs) | CC24: 4.00 kg (8.82 lbs) |
| Shipping Weight:     | CT6: 579 g (1.28 lbs)   | CT12: 736 g (1.62 lbs) | CC24: 4.40 kg (9.70 lbs) |
| Unit Capacity:       | CT6: 6  | CT12: 12               | CC24: 24                 |

### POWER

|                         |  |
|-------------------------|--|
| Power Supply Input:     | 100-240 VAC, 50-60 Hz (CT6/CT12/CC24)  |
| Power Supply Output:    | 5 VDC, 4.0 A, 20 W (CT6/CT12) / 12 VDC, 5.0 A, 60 W (CC24)   |
| Power Supply Connector: | CT6/CT12: 5.5 mm (0.22 in.) OD x 2.0 mm (0.08 in.) ID, barrel type<br>CC24: 5.5 mm (0.22 in.) OD x 2.5 mm (0.10 in.) ID, barrel type |
| Power Cord:             | CT6/CT12: 100 cm (39.37 in.) output cord<br>CC24: 175 cm (68.9 in.) input cord / 150 cm (59.05 in.) output cord                      |

### COMPLIANCE

|            |                        |
|------------|------------------------|
| Standards: | RoHS, CE, UKCA and FCC |
|------------|------------------------|



For more information, please visit [univox.eu](http://univox.eu)



Univox / Bo Edin AB  
Stockby Hantverksby 3  
SE-181 75 Lidingö, Sweden



info@univox.eu  
univox.eu



+46 8 767 18 18

