



Univox® **GO TOUR**

GT0-CT12 / GT0-CC24

Features

- Specifically designed for GoTour, offering charging and storage for up to 1 transmitter and 11 receivers (GT0-CT12), or storage, charging, and transport for up to 2 transmitters and 22 receivers (GT0-CC24)
- Securely holds transmitter with USB-C connector; receivers stay put with magnetic retention
- Charging tray can be wall mounted
- Sturdy yet lightweight Charging Case facilitates easy transport with multiple accessory compartments

Charging trays and cases

The GT0-CT12 Charging Tray and GT0-CC24 Charging Case from Univox are specifically designed for the GT0-T Transmitter and GT0-R Earpiece Receiver, offering a simple solution for storing, charging, and transporting your GoTour system.

The GT0-CT12 has a capacity for 1 transmitter and 11 receivers, while the GT0-CC24 can accommodate 2 transmitters and 22 receivers. The transmitter is securely held in place with a snug fit and a USB-C connector, while the receivers are kept in place with magnetic retention. This ensures that the charging tray can be wall-mounted using the included wall mount, eliminating the risk of receivers falling out.

Crafted from sturdy yet lightweight fabric, the Charging Case facilitates easy transport of your system to and from tours. Its compact size allows it to fit inside larger backpacks or carry bags, or it can be conveniently carried using the included shoulder strap. Additionally, the case features several compartments for organizing various accessories.

Both the CT12 and CC24 come with a PSU and a selection of plugs for regions including EU, UK, US and AUS.



Specifications

PHYSICAL

Case Color:	Black (CC24)
Tray Color:	Black (CT12/CC24)
Dimensions:	CT12 – 43 x 155 x 194 mm (1.69 x 6.10 x 7.64 in.) CC24 – 158 x 415 x 380 mm (6.22 x 16.34 x 14.96 in.)
Shipping Dimensions:	CT12 – 265 x 259 x 58 mm (10.43 x 10.2 x 2.28 in.) CC24 – 411 x 387 x 161 mm (16.18 x 15.24 x 6.34 in.)
Net Weight:	CT12 – 285 g (0.63 lbs) CC24 – 2.90 kg (6.39 lbs)
Shipping Weight:	CT12 – 900 g (1.98 lbs) CC24 – 3.25 kg (7.17 lbs)
Unit Capacity:	CT12 – 12 (1 transmitter + 11 receivers) CC24 – 24 (2 transmitter + 22 receivers)

POWER

Input:	100-240 VAC, 50-60 Hz (CT12/CC24)
Output:	5 VDC, 4.0 A, 20 W (CT12/CC24)
Connector:	5.5 mm (.22 in.) OD x 2.0 mm (.08 in.) ID, barrel type (CT12/CC24)
Cord:	100 cm (39.37 in.) output cord (CT12/CC24)

COMPLIANCE

Standards:	RoHS, CE, UKCA and FCC
------------	------------------------



For more information, please visit univox.eu



Univox / Bo Edin AB
Stockby Hantverksby 3
SE-181 75 Lidingö, Sweden



info@univox.eu
univox.eu



+46 8 767 18 18

